

Greases



Today's technically advanced vehicles & machinery demand high performance greases which are essential in meeting increasingly demanding lubrication requirements.

Wynn's have always Recognised such requirements, thus utilizing Wynn's own Research & Development Centres worldwide and its widespread customer base spanning from automotive, manufacturing and mining to the agricultural, food and resource industries to develop a first class grease range.



WYNN'S ULTRA-SUPREME GREASE



- Premium lithium soap thickened structure.
- N.L.G.I. Grade No. 2 consistency and red colour.
- Maximum structure temperature 200°C.
- Continuous operation temperature range -20°C to 160°C.
- High extreme-pressure and anti-wear properties.
- Multi purpose applications over a wide temperature range.
- Reduces equipment, bearing and component temperature.
- Resistant to channelling and water washout.

Packages Available

- 450g Cartridge
- 2.5kg Tub
- 20kg Pail
- 55kg Drum
- 175kg Drum

Product Number

- 50545
- 50525
- 50520
- 50555
- 50575

FLEET SERVICE SOLUTIONS



WYNN'S VARIPLEX MOLY GREASE



- Premium lithium soap thickened structure
- N.L.G.I. Grade No. 2 consistency and grey colour
- Maximum structure temperature 260°C
- Continuous operation temperature range -18°C to 180°C
- Extreme-pressure and shock load protection
- Molybdenum disulphide protection for specialised applications
- Long service life in harsh environments and hot conditions
- High fluid-film strength, adhesion and water resistance

Packages Available	Product Number
450g Cartridge	80319
20kg Pail	80321

WYNN'S HI-TEMP BEARING GREASE



- Premium lithium soap thickened structure
- N.L.G.I. Grade No. 2 consistency and green colour
- Maximum structure temperature 260°C
- Continuous operation temperature range -10°C to 200°C
- High extreme-pressure and anti-wear properties
- High temperature bearing lubrication applications
- Reduces bearing operating temperatures
- Ideal for heavy loaded, high wear and hot conditions

Packages Available	Product Number
450g Cartridge	50245
20kg Pail	50220
180kg Drum	50280

WYNN'S MULTIFLEET GREASE



- Premium lithium soap thickened structure
- N.L.G.I. Grade No. 3 consistency and red colour
- Maximum structure temperature 200°C
- Continuous operation temperature range -18°C to 165°C
- High adhesion and water resistant
- Extreme shock load protection of chassis components
- High extreme-pressure and anti-wear properties
- Extended ball joint life, reduced equipment temperature

Packages Available	Product Number
450g Cartridge	51045
20kg Pail	51020

WYNN'S AUTOFEED EPO GREASE



- Premium lithium soap thickened structure
- N.L.G.I. Grade No. 0 consistency and red colour
- Maximum structure temperature 190°C
- Continuous operation temperature range -23°C to 160°C
- Suitable for automatic greasers and autofeed applicators
- High anti-wear properties to extend bearing and component life
- High extreme-pressure properties for gears and chain drives
- Reduces operating temperatures, extends re-greasing intervals

Packages Available	Product Number
20kg Pail	51220

WYNN'S FOOD MACHINERY A2 GREASE



- Premium lithium soap thickened structure
- N.L.G.I. Grade No. 2 consistency and white colour
- Maximum structure temperature 232°C
- Continuous operation temperature range -25°C to 190°C
- Meets Government food regulations in USA and Australia
- Extreme-pressure and anti-wear protection for bearings
- Suitable for all food handling equipment and components
- Odourless, tasteless and provides rust protection

Packages Available	Product Number
450g Cartridge	51345
20kg Pail	51320

HIGH TEMP UNI GREASE



- New technology Calcium sulphonate base high temperature grease
- N.L.G.I. Grade No.2 consistency and brown in colour
- Excellent extreme-pressure and anti-wear properties
- Highly water resistant

Packages Available	Product Number
450g Cartridge	58500
400g Cartridge	58503
20kg Pail	58520